

AD-A094 562

FLORIDA UNIV GAINESVILLE COLL OF ENGINEERING  
ANALYTICAL INVESTIGATION OF TWO-PHASE MHD DUCT FLOWS. THE IMPIN--ETC(U)  
1978

N00014-76-C-0410

F/G 20/9

NL

UNCLASSIFIED

AD  
A094 562



END

DATE

FILED

2-84

DTIC

University of Florida  
College of Engineering  
Gainesville, FL 32611

LEVEL  
LEVEL

12

FINAL REPORT.

AD A094562

Analytical Investigation of Two-Phase MHD Duct Flows.

(as requested by ONR officials, the research title was later changes to:

The Impinging Jet of Two-Phase Flows).

Contract No. N00014-76-C-0410

15

11/1978

DTIC  
SELECTED  
FEB 4 1981  
C

1215

# ABSTRACT

— We have completed a numerical scheme for approximating the free boundary of a two dimensional inviscid incompressible jet impinging perpendicularly upon a solid wall. A Gould plot shows good agreement with an exact analytical method described by Birkhoff and Zarantonello 1957. Our method has the advantage over the analytic procedure that it allows for more realistic physical hypotheses. An example of a situation to which our method could be extended is the axisymmetric jet, for which no exact solution is know. It should be emphasized, however, that our algorithm is an approximating scheme; questions as to the speed of convergence and relative merits over the finite elements scheme used by Sarpkaya and Hiriart as reported by Gallagher and Oden 1975 in connection with the axisymmetric jet remain to be investigated.

Our work should be viewed as a first step towards developing a predictive model for the velocity and pressure distributions in the impinging jet of a two-phase medium. The complexities of this process require alternative approaches to those followed in the past. This search for new directions has been our primary objective.

DISTRIBUTION STATEMENT A  
Approved for public release;  
Distribution Unlimited

134910

gm

# A NUMERICAL SCHEME FOR THE IMPINGING JET

An algorithm is developed for predicting the free boundary of a 2-dimensional jet which impinges perpendicularly to a solid wall. The flow is assumed inviscid and incompressible.

The coordinate axes are chosen as in Fig. 1. The velocity components are denoted  $u(x,y)$  and  $v(x,y)$ . The velocity at the nozzle exit is assumed of constant magnitude  $u_0$ . The half-width of the nozzle is  $y_0$ , and the distance from nozzle exit to wall is one.





Fig. 1



Let  $\psi(x,y)$  be the streamfunction. By adding a constant, if necessary, we can assume that  $\psi$  takes the constant value zero on the jet axis (which is a streamline). We then have:

$$(1) \quad \psi(x,y) = \int_0^y u(x,y) dy$$

$$(2) \quad \frac{\partial}{\partial x} \psi(x,y) = -v(x,y)$$

[The second term in the first equation represents the flux across a vertical line segment limited between  $(x,y)$  and  $(x,0)$ ; we use the known fact that the flux across a curve is the difference in values

of the streamfunction at the endpoints.)

Algorithm. It suffices to determine the portion of the free boundary that lies above the jet axis.

Choose a positive integer  $n$ . Set  $dx = \frac{1}{n}$ , and define  $x_1 = dx$ ,  $x_2 = 2dx$ , etc. Set  $x_0 = 0$ . Suppose the point  $(x_m, y_m)$ , for some  $m$  between 0 and  $n$ , has been found to be on the free boundary, and that  $v(x_m, y_m)$  has been determined.

We first approximate  $\psi(x, y_m)$  by a 2nd order polynomial, i.e.

$$(3) \quad \psi(x, y_m) = A_m(x - x_m)^2 + B_m(x - x_m) + C_m$$

The equations (1) and (2) yield:

$$\psi(x_m, y_m) = u_0 y_0$$

$$\psi(1, y_m) = 0$$

$$\psi'(x_m, y_m) = -v(x_m, y_m)$$

which allow us to determine the constants in (3)

$$C_m = u_0 y_0$$

$$B_m = -v(x_m, y_m)$$

$$A_m = -\frac{C_m + B_m(n-m)dx}{(n-m)^2 dx^2}$$

Equations (2) and (3) yield:

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<input type="checkbox"/>
On a file	
By	
Distribution	
Availability Codes	
Dist	Avail and/or
A	Special

$$(4) \quad \psi'(x_{m+1}, y_m) = 2A_m dx + B_m = -v(x_{m+1}, y_m)$$

The slope of the free boundary at  $(x_m, y_m)$  will be:

$$(5) \quad s_m = \frac{v(x_m, y_m)}{u(x_m, y_m)} .$$

Bernoulli's equation on the free boundary gives us:

$$(6) \quad u(x_m, y_m) = \sqrt{u_0^2 - v(x_m, y_m)^2} .$$

Thus if we know  $v(x_m, y_m)$ , we can determine  $s_m$ , and approximate

$$(7) \quad y_{m+1} = y_m + s_m dx$$

[The above consists in assuming that the free boundary is a line segment between  $(x_m, y_m)$  and  $(x_{m+1}, y_{m+1})$ .]

We make a final approximation, and use (4) to get

$$(8) \quad v(x_{m+1}, y_{m+1}) = v(x_{m+1}, y_m) = -(2A_m dx + B_m) ,$$

and repeat the process. Note that now we have a new point  $(x_{m+1}, y_{m+1})$  on the free boundary, and the value  $v(x_{m+1}, y_{m+1})$ .

Since the initial values  $x_0, y_0, v(x_0, y_0) = 0$  are known, we can then obtain a sequence of points on the free boundary:  $(x_1, y_1)$ ,  $(x_2, y_2)$ , etc. The accuracy of our approximations, as can be noted,

improves when  $dx$  is taken smaller (or equivalently, when  $n$  is large). The process will stop when  $v$  is larger than  $u_0$ , for then (6) is undefined.

Comments. The above should be viewed as a first step towards developing a predictive algorithm for the velocity and pressure distributions in the jet flow. A requirement we have imposed on our model is that it be sufficiently simple and flexible to allow additional physical considerations (wall friction, etc.).

A Gould plot shows good correlation with the hodographic method. Relative merits of our scheme over Finite Elements, or other approximating schemes, remains to be investigated.

Birkhoff, G. and Zarantonello, E., Jets, Wakes, and Cavities.

Applied Mathematics and Mechanics 2, Academic Press (1957), pp37-38,

Gallanger, R. H., Oden, J. T., and Taylor, C., Finite elements in Fluids -

Volume I. John Wiley & Sons (1975), pp. 257-279.

